




SHEARS

Select Shear Model Specifications



All specifications and standard equipment are subject to change without notice. Rated at 80,000 PSI tensile and 44,000 PSI yield for mild steel.
¹With optional operator enhancement package, premium back gauge, and high speed hydraulics.
²Approximate 1 foot cut length.

Model	Capacity		Rake Angle (In/Ft)	Strokes Per Minute		# Hold Downs	Max. HD Force (Tons)	Support Arms	Motor HP	Approx. Oil Capacity (Gallons U.S.)	Basic Dimensions in Inches				Approx. Weight (Lbs)	# Hand Slots	# T- Slots
	Mild Steel	Stainless Steel		Full Length	Minimum Cut Length ²						A	B	C	D			
1/4-10	1/4"	3/16"	5/16"	12	21	11	20	0	15	80	134	84	91 ¹ / ₂	23	15,500	0	0
1/4-10 Premium¹	1/4"	3/16"	5/16"	21	40	13	24	2	20	80	134	84	88	23	15,500	3	3
1/4-12	1/4"	3/16"	5/16"	10	18	13	24	0	15	80	158	84	91 ¹ / ₂	23	19,200	0	0
1/4-12 Premium¹	1/4"	3/16"	5/16"	18	34	15	28	3	20	80	158	84	88	23	19,200	3	3
3/8-10	3/8"	1/4"	3/8"	11	28	13	31	2	20	80	131	93 ¹ / ₂	88 ¹ / ₂	24	21,500	3	3
3/8-12	3/8"	1/4"	3/8"	9	24	15	35	3	20	80	155	93 ¹ / ₂	88 ¹ / ₂	24	24,500	4	4
1/2-10	1/2"	3/8"	7/16"	10	23	13	31	2	30	80	131	102 ¹ / ₂	88 ¹ / ₂	25	27,500	3	3
1/2-12	1/2"	3/8"	7/16"	9	21	15	35	3	30	80	155	102 ¹ / ₂	88 ¹ / ₂	25	31,000	4	4

P.O. Box 457 • Hutchinson, KS 67504-0457
 800-428-3104 Fax

800-338-5471



WWW.PIRANHAFAB.COM

